

// 650AA

**Fuel-oil delivery 10 bar (150 psi)****Tube:** black conductive NBR.**Reinforcement:** high tensile textile cords.**Cover:** black conductive CR - abrasion, ozone, hydrocarbon and fire resistant.**Application:** general purpose fuel and oil delivery.**Constant operation:** -30 °C +80 °C (-22 °F +176 °F)

Alfagomma 650AA is a specially blended Anti-static fuel delivery hose offering increased flexibility at lower temperatures and excellent abrasion resistance.

Featuring synthetic textile reinforcement with weather and ozone resistant outer.

650AA Alfagomma hose is suitable for most grades of fuel including Diesel, Gasoil, Kerosene and Petrol (with an aromatic content not exceeding 50%).

Available to order by the coil. Swaged 650AA fuel hose assemblies are also available.

Suitable for both gravity and pumped applications.

Not suitable for immersion in fuel.

mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
19,0	3/4"	29,00	1,14	10	150	30	450				0,450	0,31
25,0	1"	35,00	1,38	10	150	30	450				0,570	0,39
32,0	1 1/4"	42,00	1,65	10	150	30	450				0,700	0,48
32,0	1 1/4"	44,00	1,73	10	150	30	450				0,860	0,58
35,0	1 3/8"	47,00	1,85	10	150	30	450				0,940	0,64
38,0	1 1/2"	48,00	1,89	10	150	30	450				0,820	0,56
38,0	1 1/2"	50,00	1,97	10	150	30	450				1,000	0,68
40,0	1 9/16"	52,00	2,05	10	150	30	450				1,050	0,71
45,0	1 3/4"	57,00	2,24	10	150	30	450				1,170	0,79
51,0	2"	61,00	2,40	10	150	30	450				1,090	0,74
51,0	2"	63,00	2,48	10	150	30	450				1,320	0,89
63,0	2 1/2"	75,00	2,95	10	150	30	450				1,600	1,08
76,0	3"	88,00	3,46	10	150	30	450				1,930	1,30
102,0	4"	114,00	4,49	10	150	30	450				2,610	1,76