



# ATEX Reels

## DESCRIPTION:

High capacity, spring rewind hose reels are constructed in heavy gauge powder coated mild steel. These units offer a twin pedestal design which offers ultimate performance & reliability for the most demanding of applications. Full width roller guides will prolong the hose working life along with adjustable guide arms for the most efficient, pay-out and retrieval expected in today's working environments. All units are supplied without hose, but can be furnished with our in-house selection of hose assemblies to suit your customer's needs. ATEX II certification comes as standard.

## APPLICATION:

- Air
- Low pressure oil
- Hot & Cold water
- Diesel
- Kerosene

## FEATURES:


- Constructed in powder coated mild steel.
- Atex II 94/9 IIB 2 GD c T4 T135 °C X
- Twin Pedestal Design.
- Accessible flow path for easy hose installation.
- Full width roller guide to prolong the hose life.
- Externally mounted swivel assembly for easy maintenance.
- Viton seals fitted as standard.
- Optional pivoting wall bracket available on request.
- Mounting template supplied.
- Wall, floor & Ceiling mount options.
- Ideal for vehicle mount applications.
- Auto rewind automatically stores & protects the hose.



Inlet Swivel



Atex Roller Guide



Non Sparking Latch

## TECHNICAL DETAILS:

Product Code	Hose I.D	Hose Length (m)	Working Pressure	Inlet	Outlet	Weight (Bare Reel)	Height	Width	Depth
HR-454	3/4" / 19mm	15m	20 Bar / 300 psi	1" BSP F	1" BSP F	24kgs	573mm	300mm	550mm
	3/4" / 19mm	20m	20 Bar / 300 psi	1" BSP F	1" BSP F	24kgs	573mm	300mm	550mm
	1" / 25mm	10m	20 Bar / 300 psi	1" BSP F	1" BSP F	24kgs	573mm	300mm	550mm
	1" / 25mm	15m	20 Bar / 300 psi	1" BSP F	1" BSP F	24kgs	573mm	300mm	550mm
HR-456	3/4" / 19mm	30m	20 Bar / 300 psi	1" BSP F	1" BSP F	30kgs	578mm	488mm	550mm
	3/4" / 19mm	40m	20 Bar / 300 psi	1" BSP F	1" BSP F	30kgs	578mm	488mm	550mm
	1" / 25mm	20m	20 Bar / 300 psi	1" BSP F	1" BSP F	30kgs	578mm	488mm	550mm
	1" / 25mm	30m	20 Bar / 300 psi	1" BSP F	1" BSP F	30kgs	578mm	488mm	550mm