






Diesel Electropump DC, Series: TOM 56 DC - Article:DETP0810









Flow rate (1 bar): 47 lt/min Voltage: 12V Max Pressure: 2,5 Bar IN: F 1" BSP OUT: F 1" BSP Suction: 2,5 mt Self Priming: Automatic Integrated filter: 130um Bleeder valve: Included Motion transmission: Crankshaft Type rotor: 5 vain Pump Body: Cast iron By-pass: Included Seal: 6 bar Mechanical seal Anti flooding motor protection: Included Fuse: Amp Duty cicle: S2 30min Engine Rotation: 3400 rpm Power: 75 Watt Ampere: 36 Amp. Switch ON-OFF: Included Electric Wire: Clamp wire 1,8mt Noisiness: 80 db Operating temperature: +40 / -10 °C Packaging: 32x15x15h cm	Technical features:	
Max Pressure: 2,5 Bar IN: F 1" BSP OUT: F 1" BSP Suction: 2,5 mt Self Priming: Automatic Integrated filter: 130um Bleeder valve: Included Motion transmission: Crankshaft Type rotor: 5 vain Pump Body: Cast iron By-pass: Included Seal: 6 bar Mechanical seal Anti flooding motor protection: Included Fuse: Amp Duty cicle: S2 30min Engine Rotation: 3400 rpm Power: 75 Watt Ampere: 36 Amp. Switch ON-OFF: Included Electric Wire: Clamp wire 1,8mt Noisiness: 80 db Operating temperature: +40 / -10 °C Packaging: 32x15x15h cm	Flow rate (1 bar):	47 lt/min
IN: F 1" BSP OUT: F 1" BSP Suction: 2,5 mt Self Priming: Automatic Integrated filter: 130um Bleeder valve: Included Motion transmission: Crankshaft Type rotor: 5 vain Pump Body: Cast iron By-pass: Included Seal: 6 bar Mechanical seal Anti flooding motor protection: Included Fuse: Amp Duty cicle: S2 30min Engine Rotation: 3400 rpm Power: 75 Watt Ampere: 36 Amp. Switch ON-OFF: Included Electric Wire: Clamp wire 1,8mt Noisiness: 80 db Operating temperature: +40 / -10 °C Packaging: 32x15x15h cm	Voltage:	12V
OUT: F 1" BSP Suction: 2,5 mt Self Priming: Automatic Integrated filter: 130um Bleeder valve: Included Motion transmission: Crankshaft Type rotor: 5 vain Pump Body: Cast iron By-pass: Included Seal: 6 bar Mechanical seal Anti flooding motor protection: Included Fuse: Amp Duty cicle: S2 30min Engine Rotation: 3400 rpm Power: 75 Watt Ampere: 36 Amp. Switch ON-OFF: Included Electric Wire: Clamp wire 1,8mt Noisiness: 80 db Operating temperature: +40 / -10 °C Packaging: 32x15x15h cm	Max Pressure:	2,5 Bar
Suction: 2,5 mt Self Priming: Automatic Integrated filter: 130um Bleeder valve: Included Motion transmission: Crankshaft Type rotor: 5 vain Pump Body: Cast iron By-pass: Included Seal: 6 bar Mechanical seal Anti flooding motor protection: Included Fuse: Amp Duty cicle: S2 30min Engine Rotation: 3400 rpm Power: 75 Watt Ampere: 36 Amp. Switch ON-OFF: Included Electric Wire: Clamp wire 1,8mt Noisiness: 80 db Operating temperature: +40 / -10 °C Packaging: 32x15x15h cm	IN:	F 1" BSP
Self Priming: Automatic Integrated filter: 130um Bleeder valve: Included Motion transmission: Crankshaft Type rotor: 5 vain Pump Body: Cast iron By-pass: Included Seal: 6 bar Mechanical seal Anti flooding motor protection: Included Fuse: Amp Duty cicle: S2 30min Engine Rotation: 3400 rpm Power: 75 Watt Ampere: 36 Amp. Switch ON-OFF: Included Electric Wire: Clamp wire 1,8mt Noisiness: 80 db Operating temperature: +40 / -10 °C Packaging: 32x15x15h cm	OUT:	F 1" BSP
Integrated filter: 130um Bleeder valve: Included Motion transmission: Crankshaft Type rotor: 5 vain Pump Body: Cast iron By-pass: Included Seal: 6 bar Mechanical seal Anti flooding motor protection: Included Fuse: Amp Duty cicle: S2 30min Engine Rotation: 3400 rpm Power: 75 Watt Ampere: 36 Amp. Switch ON-OFF: Included Electric Wire: Clamp wire 1,8mt Noisiness: 80 db Operating temperature: +40 / -10 °C Packaging: 32x15x15h cm	Suction:	2,5 mt
Bleeder valve: Motion transmission: Crankshaft Type rotor: 5 vain Pump Body: Cast iron By-pass: Included Seal: 6 bar Mechanical seal Anti flooding motor protection: Included Fuse: Amp Duty cicle: S2 30min Engine Rotation: 3400 rpm Power: 75 Watt Ampere: 36 Amp. Switch ON-OFF: Included Electric Wire: Clamp wire 1,8mt Noisiness: 80 db Operating temperature: +40 / -10 °C Packaging: 32x15x15h cm	Self Priming:	Automatic
Motion transmission: Crankshaft Type rotor: 5 vain Pump Body: Cast iron By-pass: Included Seal: 6 bar Mechanical seal Anti flooding motor protection: Included Fuse: Amp Duty cicle: S2 30min Engine Rotation: 3400 rpm Power: 75 Watt Ampere: 36 Amp. Switch ON-OFF: Included Electric Wire: Clamp wire 1,8mt Noisiness: 80 db Operating temperature: +40 / -10 °C Packaging: 32x15x15h cm	Integrated filter:	130um
Type rotor: 5 vain Pump Body: Cast iron By-pass: Included Seal: 6 bar Mechanical seal Anti flooding motor protection: Included Fuse: Amp Duty cicle: S2 30min Engine Rotation: 3400 rpm Power: 75 Watt Ampere: 36 Amp. Switch ON-OFF: Included Electric Wire: Clamp wire 1,8mt Noisiness: 80 db Operating temperature: +40 / -10 °C Packaging: 32x15x15h cm	Bleeder valve:	Included
Pump Body: Cast iron By-pass: Included Seal: 6 bar Mechanical seal Anti flooding motor protection: Included Fuse: Amp Duty cicle: S2 30min Engine Rotation: 3400 rpm Power: 75 Watt Ampere: 36 Amp. Switch ON-OFF: Included Electric Wire: Clamp wire 1,8mt Noisiness: 80 db Operating temperature: +40 / -10 °C Packaging: 32x15x15h cm	Motion transmission:	Crankshaft
By-pass: Included Seal: 6 bar Mechanical seal Anti flooding motor protection: Included Fuse: Amp Duty cicle: S2 30min Engine Rotation: 3400 rpm Power: 75 Watt Ampere: 36 Amp. Switch ON-OFF: Included Electric Wire: Clamp wire 1,8mt Noisiness: 80 db Operating temperature: +40 / -10 °C Packaging: 32x15x15h cm	Type rotor:	5 vain
Seal: Anti flooding motor protection: Included Fuse: Amp Duty cicle: S2 30min Engine Rotation: 3400 rpm Power: 75 Watt Ampere: 36 Amp. Switch ON-OFF: Included Electric Wire: Clamp wire 1,8mt Noisiness: 80 db Operating temperature: +40 / -10 °C Packaging: 32x15x15h cm	Pump Body:	Cast iron
Anti flooding motor protection: Included Fuse: Amp Duty cicle: S2 30min Engine Rotation: 3400 rpm Power: 75 Watt Ampere: 36 Amp. Switch ON-OFF: Included Electric Wire: Clamp wire 1,8mt Noisiness: 80 db Operating temperature: +40 / -10 °C Packaging: 32x15x15h cm	By-pass:	Included
protection: Included Fuse: Amp Duty cicle: S2 30min Engine Rotation: 3400 rpm Power: 75 Watt Ampere: 36 Amp. Switch ON-OFF: Included Electric Wire: Clamp wire 1,8mt Noisiness: 80 db Operating temperature: +40 / -10 °C Packaging: 32x15x15h cm	Seal:	6 bar Mechanical seal
Fuse: Amp Duty cicle: S2 30min Engine Rotation: 3400 rpm Power: 75 Watt Ampere: 36 Amp. Switch ON-OFF: Included Electric Wire: Clamp wire 1,8mt Noisiness: 80 db Operating temperature: +40 / -10 °C Packaging: 32x15x15h cm		Included
Duty cicle: S2 30min Engine Rotation: 3400 rpm Power: 75 Watt Ampere: 36 Amp. Switch ON-OFF: Included Electric Wire: Clamp wire 1,8mt Noisiness: 80 db Operating temperature: +40 / -10 °C Packaging: 32x15x15h cm		
Engine Rotation: 3400 rpm Power: 75 Watt Ampere: 36 Amp. Switch ON-OFF: Included Electric Wire: Clamp wire 1,8mt Noisiness: 80 db Operating temperature: +40 / -10 °C Packaging: 32x15x15h cm	Duty cicle:	·
Power: 75 Watt Ampere: 36 Amp. Switch ON-OFF: Included Electric Wire: Clamp wire 1,8mt Noisiness: 80 db Operating temperature: +40 / -10 °C Packaging: 32x15x15h cm	<u> </u>	3400 rpm
Switch ON-OFF: Included Electric Wire: Clamp wire 1,8mt Noisiness: 80 db Operating temperature: +40 / -10 °C Packaging: 32x15x15h cm		
Electric Wire: Clamp wire 1,8mt Noisiness: 80 db Operating temperature: +40 / -10 °C Packaging: 32x15x15h cm	Ampere:	36 Amp.
Noisiness: 80 db Operating temperature: +40 / -10 °C Packaging: 32x15x15h cm	Switch ON-OFF:	Included
Operating temperature: +40 / -10 °C Packaging: 32x15x15h cm	Electric Wire:	Clamp wire 1,8mt
Packaging: 32x15x15h cm	Noisiness:	80 db
	Operating temperature:	+40 / -10 °C
Weight: 6.5 Kg	Packaging:	32x15x15h cm
7,0,g.m. 0,0 Ng	Weight:	6,5 Kg

