

E300

FEATURES

- HIGH-FLOW PUMP
- STURDY STRUCTURE
- HEAVY DUTY APPLICATION
- IP44

The PIUSI E300 is an electric pump with open impeller suitable for all applications in which high-flows are required. Thus, it is the ideal equipment for topping up and transferring diesel from drums. It comes with an incorporated check valve in the suction port to prevent the siphon effect while ensuring automatic re-priming.

PERFORMANCE

UP TO
300 L/MIN

FLOW RATE

AC
CONTINUOUS DUTY

POWER

1,7 BAR
MAX

OPERATING PRESSURE



E300




PACKAGING

CODE	WEIGHT		PACKAGING		
	KG	LBS	MM	INCH	PCS/BOX
FO0321000	27	59	220X420X330	8,7X16,5X13	1

B10 ANY BIODIESEL
 A AIR
 A ANTIFREEZE
 Ad AdBlue®
 B BIODIESEL
 D DIESEL
 F FOOD
 G GASOLINE
 G GREASE
 K KEROSENE
 O OIL
 W WATER
 W WINDSCREEN


CHART



TYPE OF FLUID DIESEL

TEMPERATURE 10°C

DIMENSIONS



Dimensions expressed in millimeters

IN THE BOX

- E300 PUMP
- INSTRUCTION MANUAL

DETAILS



MATERIALS

- BODY: CAST IRON
- OPEN IMPELLER: CAST IRON
- SEAL: VITON
- SHAFT: STEEL

TECHNICAL DATA

CODE	DESCRIPTION	FLUIDS TYPE	FLOW RATE		VOLTAGE			RPM	INLET OUTLET
			L/MIN	GPM	AC VOLT/HZ	POWER WATT	AMP. MAX.		
FO0321000	E 300	D	300	80	230/50	1500	7	2580	2"