







AdBlue® trolley-200 I-10 I/min

ZVAUD-PP-EBZDU-230 V-50 Hz

Item number: EAN:

25 338 770 4048358707987

Technical data	
Pump Connecting cable, length (m):	2
Hydraulic data	-
Pump design:	diaphragm pump, selfpriming
Delivery rate under free discharge	
(l/min):	14
Discharge pressure up to (bar):	1,7
Pumping media:	AdBlue®, water
Motor data	
Voltage (V):	230
Frequency (Hz):	50/60
Power consumption (A):	1,5
Duty cycle (min):	continuous operation – a real endurance runner
Safety class:	IP66
Trolley load (kg):	200
Dimensions LxWxH (mm):	1200 x 840 x 270
Weight (kg):	41,4

Specification

- AdBlue® supply system, mobile
- For 200/220 I container
- Diaphragm pump, selfpriming (25 284)
- Automatic nozzle for AdBlue® with swivel (ZVAUD-PP) (23 171 961)
- In-line meter, digital, for AdBlue® (EBZDU) (23 190 870)
- Suction tube for IBC (83 396)
- AdBlue® suction hose, DN 19, 1 m, with SEC adapter and bend 90° with spout (25) 657)
- AdBlue® discharge hose, DN 13, 4 m, with bend 90° G 1" female and swivel joint for automatic nozzle valve ZVAUD 10 I (25 683)
- Trolley (17 077)

Special notes

- Dispensing valve exchange container with water reservoir
- Precise oval gear meter over entire discharge amount made of stainless steel
- Displays: Indication of partial quantity equals current filling level (resettable to zero) + total quantity (resettable to zero) + total quantity (not resettable to zero)

Packaging

Packaging: Dimensions LxWxH (mm): Weight including package (kg): Packing unit:

Carton 950 x 840 x 270 48.39 1.0

Commercial Fuel Solutions Limited

H1, Adanac North, Southampton, Hampshire, GB, SO16 0BT | 02380 118670 service@commercialfuelsolutions.co.uk | commercialfuelsolutions.co.uk

